

FRL Combination Units

(Filter + Regulator + Lubricator)



- Pressure Gauge Included
- 5 Micron Filter Element
- Push / Pull Adjusting Knob
- Bowl Guard Standard (except miniature FRL)
- Modular Construction
- 150 psig Maximum Pressure

**How to order
or for information:**

1.888.426.8111



Don't forget to order ...

- Airline Lubricant (pg. 8)
- Shut-off Valves (pg. 10)

Standard FRL Combinations

Standard FRL Combination Manual Drain		
Item	Port Size	SCFM*
22-204	1/4" NPT	40
22-306	3/8" NPT	60
22-456	1/2" NPT (Compact Body)	70
22-408	1/2" NPT	105
22-510	3/4" NPT	110
22-612	1" NPT	260

Also Available:

- Metal Bowls
- 2 psig - 25 psig Pressure Range
- 2 psig - 60 psig Pressure Range
- Replacement Bowls

Standard FRL Combination Automatic Drain		
Item	Port Size	SCFM*
22-205	1/4" NPT	40
22-307	3/8" NPT	60
22-457	1/2" NPT (Compact Body)	70
22-409	1/2" NPT	105
22-511	3/4" NPT	110
22-613	1" NPT	260

* SCFM at 100 psig inlet and 80 psig reduced pressure

* SCFM at 100 psig inlet and 80 psig reduced pressure

Miniature FRL Combinations

Replacement Filter Elements

Pressure Gauge and Mounting Bracket Included

*Replace the filter element yearly
or at a 10 psi pressure drop*

Miniature FRL Combination Manual Drain		
Item	Port Size	SCFM*
22-100	1/8" NPT	10
22-202	1/4" NPT	10



Replacement Filter Elements	
FRL Combo	Element
22-100/22-202	24-801
22-204/22-205	24-803
22-306/22-307	24-803
22-408/22-409	24-805
22-456/22-457	24-803
22-510/22-511	24-805
22-612/22-613	24-807

* SCFM at 100 psig inlet and 80 psig reduced pressure